

DECLARATION OF PERFORMANCE

No: SVL-035E

1. Identification code of the produce type:	NA2XY
2. Intended use or uses of the construction product , in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Supply of electricity in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke
3. Registered trade name and Manufacturer address:	SEVAL KABLO AYD. CİH. İTH. İHR. SAN. TİC. A.Ş Hacıyüplü mah. 3119 sok. no: 5 Merkezefendi DENİZLİ/ TURKEY E: qc@sevalkablo.com W: www.sevalkablo.com
4. Notified Body,Code,Harmonized standard:	TURKISH STANDARDS INSTITUTION (TSE) NB No. 1783 EN 50575:2014+A1:2016
5. System or systems of assessment and verification of constancy of performance :	System 3
6. Declared Performance :	E _{ca}
7.Dangerous substances :	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by
MAY 2017 DENİZLİ/TURKEY

Murat KAÇAMAZ
Plant Manager



DECLARATION OF PERFORMANCE

Scope of the Document

No: SVL-035E

CABLE TYPE: NA2XY

VOLTAGE: 0.6/1 kV

SINGLE CONSTRUCTION: AL/XLPE/PVC

MULTI CONSTRUCTION: AL/XLPE/PVC/PVC

Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area
1	16mm ²	2	16mm ²	4	10mm ²
1	25mm ²	2	25mm ²	4	16mm ²
1	35mm ²	3	10mm ²	4	25mm ²
1	50mm ²	3	16mm ²	4	35mm ²
1	70mm ²	3	25mm ²	4	50mm ²
1	95mm ²	3	35mm ²	4	70mm ²
1	120mm ²	3	50mm ²	4	95mm ²
1	150mm ²	3	70mm ²	4	120mm ²
1	185mm ²	3	95mm ²	4	150mm ²
1	240mm ²	3	120mm ²	4	185mm ²
1	300mm ²	3	150mm ²	4	240mm ²
1	400mm ²	3	185mm ²	4	300mm ²
		3	240mm ²	4	400mm ²
		3	300mm ²		

Signed for and behalf of the manufacturer by
MAY 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager

DECLARATION OF PERFORMANCE

Scope of the Document

No: SVL-035E

CABLE TYPE: NA2XY

VOLTAGE: 0.6/1 kV

SINGLE CONSTRUCTION: AL/XLPE/PVC

MULTI CONSTRUCTION: AL/XLPE/PVC/PVC

Number Of Cores	Cross-Sectional Area	Number Of Cores	Cross-Sectional Area
5	10mm ²	3	16/10mm ²
5	16mm ²	3	25/16mm ²
5	25mm ²	3	35/16mm ²
5	35mm ²	3	50/25mm ²
5	50mm ²	3	70/35mm ²
5	70mm ²	3	95/50mm ²
5	95mm ²	3	120/70mm ²
5	120mm ²	3	150/70mm ²
5	150mm ²	3	185/95mm ²
5	185mm ²	3	240/120mm ²
5	240mm ²	3	300/150mm ²
5	300mm ²	3	400/185mm ²

Signed for and behalf of the manufacturer by
MAY 2017 DENIZLI/TURKEY

Murat KAÇAMAZ
Plant Manager